

**5** = 20 mm<sup>2</sup>**21****Other designs in series 21**

The following other designs can be found from page:

- |                           |        |
|---------------------------|--------|
| ▶ Brass / Steel           | P. 30  |
| ▶ Stainless Steel         | P. 192 |
| ▶ Thermoplastic           | P. 232 |
| ▶ Medical Technology (MD) | P. 256 |
| ▶ Safety                  | P. 270 |

**Technical Description**

Coded industrial coupling system developed on the basis of series 21 with above-average flow rate for liquid and gaseous media.

Coupling system with single-hand operation. The mechanical coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling, which is complemented by the color coding of the anodised sleeves.

Double shut-off version available on request.

**Working Temperature\***

-20°C up to +100°C (NBR)  
depending on the medium.

\* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure\*\***

35 bar

\*\* maximum static working pressure with safety factor 4 to 1.

**Material**



**Coupling:** Brass

**Plug:** Brass or Brass nickel plated

**Seals:** NBR

**Interchangeability**






- Rectus Design

**Flow diagrams****Air****Water**












# Couplings – with valve

# Series 21KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	● Part Number	▲ Part Number	● Part Number	● Part Number
 Male Thread	G 1/8	14		47	7		16			blank	21KAAW10MPX0	21KAAW10MPX3	21KAAW10MPX6	21KAAW10MPX8
	G 1/8	14		47	7		16			nickel plated	21KAAW10MPN0	21KAAW10MPN3	21KAAW10MPN6	21KAAW10MPN8
	G 1/4	17		47	9		16			blank	21KAAW13MPX0	21KAAW13MPX3	21KAAW13MPX6	21KAAW13MPX8
	G 1/4	17		47	9		16			nickel plated	21KAAW13MPN0	21KAAW13MPN3	21KAAW13MPN6	21KAAW13MPN8
 Female Thread	G 1/8	14		47	7		16			blank	21KAIW10MPX0	21KAIW10MPX3	21KAIW10MPX6	21KAIW10MPX8
	G 1/8	14		47	7		16			nickel plated	21KAIW10MPN0	21KAIW10MPN3	21KAIW10MPN6	21KAIW10MPN8
	G 1/4	17		47	9		16			blank	21KAIW13MPX0	21KAIW13MPX3	21KAIW13MPX6	21KAIW13MPX8
	G 1/4	17		47	9		16			nickel plated	21KAIW13MPN0	21KAIW13MPN3	21KAIW13MPN6	21KAIW13MPN8
 Hose Barb	4 mm	14		69	17		16			blank	21KATF04MPX0	21KATF04MPX3	21KATF04MPX6	21KATF04MPX8
	4 mm	14		69	17		16			nickel plated	21KATF04MPN0	21KATF04MPN3	21KATF04MPN6	21KATF04MPN8
	6 mm	14		69	17		16			blank	21KATF06MPX0	21KATF06MPX3	21KATF06MPX6	21KATF06MPX8
	6 mm	14		69	17		16			nickel plated	21KATF06MPN0	21KATF06MPN3	21KATF06MPN6	21KATF06MPN8
	8 mm	14		69	17		16			blank	21KATF08MPX0	21KATF08MPX3	21KATF08MPX6	21KATF08MPX8
	8 mm	14		69	17		16			nickel plated	21KATF08MPN0	21KATF08MPN3	21KATF08MPN6	21KATF08MPN8
 with Plastic Hose Connection	4 x 6 mm	14		51	7	6	16		M10x1	blank	21KAKO06MPX0	21KAKO06MPX3	21KAKO06MPX6	21KAKO06MPX8
	4 x 6 mm	14		51	7	6	16		M10x1	nickel plated	21KAKO06MPN0	21KAKO06MPN3	21KAKO06MPN6	21KAKO06MPN8
	6 x 8 mm	14		51	7	6	16		M12x1	blank	21KAKO08MPX0	21KAKO08MPX3	21KAKO08MPX6	21KAKO08MPX8
	6 x 8 mm	14		51	7	6	16		M12x1	nickel plated	21KAKO08MPN0	21KAKO08MPN3	21KAKO08MPN6	21KAKO08MPN8
 Panel Mount with Hose Barb	4 mm	14	14	69	14	17	16	4	M10x1	blank	21KATS04MPX0	21KATS04MPX3	21KATS04MPX6	21KATS04MPX8
	4 mm	14	14	69	14	17	16	4	M10x1	nickel plated	21KATS04MPN0	21KATS04MPN3	21KATS04MPN6	21KATS04MPN8
	6 mm	14	17	69	14	17	16	4	M12x1	blank	21KATS06MPX0	21KATS06MPX3	21KATS06MPX6	21KATS06MPX8
	6 mm	14	17	69	14	17	16	4	M12x1	nickel plated	21KATS06MPN0	21KATS06MPN3	21KATS06MPN6	21KATS06MPN8
	8 mm	14	17	69	14	17	16	4	M12x1	blank	21KATS08MPX0	21KATS08MPX3	21KATS08MPX6	21KATS08MPX8

**Plugs – without valve** **Series 21KA**

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	 Part Number	 Part Number	 Part Number	 Part Number
 <p>Male Thread</p>	G 1/8	17		39,5	7					blank	21SFAW10MXX0	21SFAW10MXX3	21SFAW10MXX6	21SFAW10MXX8
	G 1/8	17		39,5	7					nickel plated	21SFAW10MXN0	21SFAW10MXN3	21SFAW10MXN6	21SFAW10MXN8
	G 1/4	17		41,5	9					blank	21SFAW13MXX0	21SFAW13MXX3	21SFAW13MXX6	21SFAW13MXX8
	G 1/4	17		41,5	9					nickel plated	21SFAW13MXN0	21SFAW13MXN3	21SFAW13MXN6	21SFAW13MXN8
 <p>Female Thread</p>	G 1/8	17		38,5	5					blank	21SFIW10MXX0	21SFIW10MXX3	21SFIW10MXX6	21SFIW10MXX8
	G 1/8	17		38,5	5					nickel plated	21SFIW10MXN0	21SFIW10MXN3	21SFIW10MXN6	21SFIW10MXN8
	G 1/4	17		39	7					blank	21SFIW13MXX0	21SFIW13MXX3	21SFIW13MXX6	21SFIW13MXX8
	G 1/4	17		39	7					nickel plated	21SFIW13MXN0	21SFIW13MXN3	21SFIW13MXN6	21SFIW13MXN8
 <p>Hose Barb</p>	4 mm			47	17		15			blank	21SFTF04MXX0	21SFTF04MXX3	21SFTF04MXX6	21SFTF04MXX8
	4 mm			47	17		15			nickel plated	21SFTF04MXN0	21SFTF04MXN3	21SFTF04MXN6	21SFTF04MXN8
	6 mm			47	17		15			blank	21SFTF06MXX0	21SFTF06MXX3	21SFTF06MXX6	21SFTF06MXX8
	6 mm			47	17		15			nickel plated	21SFTF06MXN0	21SFTF06MXN3	21SFTF06MXN6	21SFTF06MXN8
 <p>with Plastic Hose Connection</p>	4 x 6 mm			43	7	6	15		M10x1	blank	21SFKO06MXX0	21SFKO06MXX3	21SFKO06MXX6	21SFKO06MXX8
	4 x 6 mm			43	7	6	15		M10x1	nickel plated	21SFKO06MXN0	21SFKO06MXN3	21SFKO06MXN6	21SFKO06MXN8
	6 x 8 mm			43,5	7	6	15		M12x1	blank	21SFKO08MXX0	21SFKO08MXX3	21SFKO08MXX6	21SFKO08MXX8
	6 x 8 mm			43,5	7	6	15		M12x1	nickel plated	21SFKO08MXN0	21SFKO08MXN3	21SFKO08MXN6	21SFKO08MXN8
 <p>Panel Mount with Hose Barb</p>	4 mm	17	14	63	17	14		4	M10x1	blank	21SFTS04MXX0	21SFTS04MXX3	21SFTS04MXX6	21SFTS04MXX8
	4 mm	17	14	63	17	14		4	M10x1	nickel plated	21SFTS04MXN0	21SFTS04MXN3	21SFTS04MXN6	21SFTS04MXN8
	6 mm	17	17	63	17	14		4	M12x1	blank	21SFTS06MXX0	21SFTS06MXX3	21SFTS06MXX6	21SFTS06MXX8
	6 mm	17	17	63	17	14		4	M12x1	nickel plated	21SFTS06MXN0	21SFTS06MXN3	21SFTS06MXN6	21SFTS06MXN8

**Other designs in series 25**

The following other designs can be found from page:

- |                       |        |
|-----------------------|--------|
| ▶ Brass / Steel       | P. 98  |
| ▶ Stainless Steel     | P. 208 |
| ▶ Safety              | P. 274 |
| ▶ Safety Self-Venting | P. 294 |

**Technical Description**

Coded industrial coupling system developed on the basis of series 25. Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The mechanical coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling, which is complemented by the color coding of the anodised sleeves. Double shut-off and straight-through couplings are available upon request. Cannot be interconnected with the Rectus standard 25 series.

**Working Temperature\***

-20°C up to +100°C (NBR) depending on the medium.

\* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure\*\***

**35 bar**



\*\* maximum static working pressure with safety factor 4 to 1.

**Material**

**Coupling:** Brass  
**Plug:** Brass or Brass nickel plated  
**Seals:** NBR

**Interchangeability**

- Rectus Design

**Flow diagrams****Air****Water**



# Couplings – with valve










# Series 25KA

Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version				
										Part Number	Part Number	Part Number	Part Number
<p>Male Thread</p>	G 1/4	19		57,5	12		23		blank	25KAAW13BPX0	25KAAW13BPX3	25KAAW13BPX6	25KAAW13BPX8
	G 1/4	19		57,5	12		23		nickel plated	25KAAW13BPN0	25KAAW13BPN3	25KAAW13BPN6	25KAAW13BPN8
	G 3/8	19		57,5	12		23		blank	25KAAW17BPX0	25KAAW17BPX3	25KAAW17BPX6	25KAAW17BPX8
	G 3/8	19		57,5	12		23		nickel plated	25KAAW17BPN0	25KAAW17BPN3	25KAAW17BPN6	25KAAW17BPN8
	G 1/2	22		61	17		23		blank	25KAAW21BPX0	25KAAW21BPX3	25KAAW21BPX6	25KAAW21BPX8
	G 1/2	22		61	17		23		nickel plated	25KAAW21BPN0	25KAAW21BPN3	25KAAW21BPN6	25KAAW21BPN8
<p>Female Thread</p>	G 1/4	19		55	10		23		blank	25KAIW13BPX0	25KAIW13BPX3	25KAIW13BPX6	25KAIW13BPX8
	G 1/4	19		55	10		23		nickel plated	25KAIW13BPN0	25KAIW13BPN3	25KAIW13BPN6	25KAIW13BPN8
	G 3/8	19		55	9		23		blank	25KAIW17BPX0	25KAIW17BPX3	25KAIW17BPX6	25KAIW17BPX8
	G 3/8	19		55	9		23		nickel plated	25KAIW17BPN0	25KAIW17BPN3	25KAIW17BPN6	25KAIW17BPN8
	G 1/2	24		58	12		23		blank	25KAIW21BPX0	25KAIW21BPX3	25KAIW21BPX6	25KAIW21BPX8
	G 1/2	24		58	12		23		nickel plated	25KAIW21BPN0	25KAIW21BPN3	25KAIW21BPN6	25KAIW21BPN8
<p>Hose Barb</p>	6 mm	19		74	25		23		blank	25KATF06BPX0	25KATF06BPX3	25KATF06BPX6	25KATF06BPX8
	6 mm	19		74	25		23		nickel plated	25KATF06BPN0	25KATF06BPN3	25KATF06BPN6	25KATF06BPN8
	9 mm	19		74	25		23		blank	25KATF09BPX0	25KATF09BPX3	25KATF09BPX6	25KATF09BPX8
	9 mm	19		74	25		23		nickel plated	25KATF09BPN0	25KATF09BPN3	25KATF09BPN6	25KATF09BPN8
	13 mm	19		74	25		23		blank	25KATF13BPX0	25KATF13BPX3	25KATF13BPX6	25KATF13BPX8
	13 mm	19		74	25		23		nickel plated	25KATF13BPN0	25KATF13BPN3	25KATF13BPN6	25KATF13BPN8
<p>with Plastic Hose Connection</p>	6 x 8 mm	19		61	7	6	23	M12x1	blank	25KAKO08BPX0	25KAKO08BPX3	25KAKO08BPX6	25KAKO08BPX8
	6 x 8 mm	19		61	7	6	23	M12x1	nickel plated	25KAKO08BPN0	25KAKO08BPN3	25KAKO08BPN6	25KAKO08BPN8
	8 x 10 mm	19		65	9	8	23	M16x1	blank	25KAKO10BPX0	25KAKO10BPX3	25KAKO10BPX6	25KAKO10BPX8
	8 x 10 mm	19		65	9	8	23	M16x1	nickel plated	25KAKO10BPN0	25KAKO10BPN3	25KAKO10BPN6	25KAKO10BPN8



# Plugs – without valve

# Series 26SF

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	 Part Number	 Part Number	 Part Number	 Part Number
 <p>Male Thread</p>	G 1/4	17		36,5	9					blank	26SFAW13MXX0	26SFAW13MXX3	26SFAW13MXX6	26SFAW13MXX8
	G 1/4	17		36,5	9					nickel plated	26SFAW13MXN0	26SFAW13MXN3	26SFAW13MXN6	26SFAW13MXN8
	G 3/8	19		41,5	12					blank	26SFAW17MXX0	26SFAW17MXX3	26SFAW17MXX6	26SFAW17MXX8
	G 3/8	19		41,5	12					nickel plated	26SFAW17MXN0	26SFAW17MXN3	26SFAW17MXN6	26SFAW17MXN8
 <p>Female Thread</p>	G 1/4	17		36,5	8					blank	26SFIW13MXX0	26SFIW13MXX3	26SFIW13MXX6	26SFIW13MXX8
	G 1/4	17		36,5	8					nickel plated	26SFIW13MXN0	26SFIW13MXN3	26SFIW13MXN6	26SFIW13MXN8
	G 3/8	19		36,5	8					blank	26SFIW17MXX0	26SFIW17MXX3	26SFIW17MXX6	26SFIW17MXX8
	G 3/8	19		36,5	8					nickel plated	26SFIW17MXN0	26SFIW17MXN3	26SFIW17MXN6	26SFIW17MXN8
 <p>Hose Barb</p>	6 mm			50,5	25		15			blank	26SFTF06MXX0	26SFTF06MXX3	26SFTF06MXX6	26SFTF06MXX8
	6 mm			50,5	25		15			nickel plated	26SFTF06MXN0	26SFTF06MXN3	26SFTF06MXN6	26SFTF06MXN8
	9 mm			50,5	25		15			blank	26SFTF09MXX0	26SFTF09MXX3	26SFTF09MXX6	26SFTF09MXX8
	9 mm			50,5	25		15			nickel plated	26SFTF09MXN0	26SFTF09MXN3	26SFTF09MXN6	26SFTF09MXN8
	13 mm			50,5	25		15			blank	26SFTF13MXX0	26SFTF13MXX3	26SFTF13MXX6	26SFTF13MXX8
	13 mm			50,5	25		15			nickel plated	26SFTF13MXN0	26SFTF13MXN3	26SFTF13MXN6	26SFTF13MXN8
 <p>with Plastic Hose Connection</p>	6 x 8 mm			43,5	7	6	15		M12x1	blank	26SFKO08MXX0	26SFKO08MXX3	26SFKO08MXX6	26SFKO08MXX8
	6 x 8 mm			43,5	7	6	15		M12x1	nickel plated	26SFKO08MXN0	26SFKO08MXN3	26SFKO08MXN6	26SFKO08MXN8
	8 x 10 mm	17		43,5	8,5	8,5			M16x1	blank	26SFKO10MXX0	26SFKO10MXX3	26SFKO10MXX6	26SFKO10MXX8
	8 x 10 mm	17		43,5	8,5	8,5			M16x1	nickel plated	26SFKO10MXN0	26SFKO10MXN3	26SFKO10MXN6	26SFKO10MXN8
 <p>Panel Mount with Hose Barb</p>	6 mm	17	17	60	17	14		4	M12x1	blank	26SFTS06MXX0	26SFTS06MXX3	26SFTS06MXX6	26SFTS06MXX8
	6 mm	17	17	60	17	14		4	M12x1	nickel plated	26SFTS06MXN0	26SFTS06MXN3	26SFTS06MXN6	26SFTS06MXN8

Nominal Diameter

**7,4** = 42 mm<sup>2</sup>

Rectus Series

**65-67****Technical Description**

Quick connect coupling system with coding developed specifically for use with fuel gas and oxygen on pressure regulators / welding torches etc. Our „RectuKey“ coding system prevents mixing up media. Up to three different media can be safely (non-interchangeable) connected with the standard version.

**Working Temperature\***

-20°C up to +100°C (NBR)  
depending on the medium.

\* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure\*\*****35 bar**



\*\* maximum static working pressure with safety factor 4 to 1.

**Material**

**Coupling:** Brass ungreased

**Plug:** Brass ungreased



**Seals:** FKM or EPDM

**Flow diagrams****Air****Water**



## Couplings – with valve



## Series 65-67KS

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	Seal	Version	Part Number
 <p>Female Thread</p>	G 1/4 right	19		69,5	10		22		FKM	Oxygen	65KSIW13MVX
	G 3/8 right	19		69,5	9		22		FKM	Oxygen	65KSIW17MVX
	G 1/4 left	19		69,5	10		22		EPDM	Fuel gas	66KSIL13MEX
	G 3/8 left	19		69,5	10		22		EPDM	Fuel gas	66KSIL17MEX
	G 1/4 left	19		69,5	10		22		FKM	Var. Media	67KSIL13MVX
	G 3/8 left	19		69,5	10		22		FKM	Var. Media	67KSIL17MVX
 <p>Hose Barb</p>	6 mm	19		90	33		22		FKM	Oxygen	65KSTF06MVX
	9 mm	19		90	33		22		FKM	Oxygen	65KSTF09MVX
	6 mm	19		90	33		22		EPDM	Fuel gas	66KSTF06MEX
	9 mm	19		90	33		22		EPDM	Fuel gas	66KSTF09MEX
	6 mm	19		90	33		22		FKM	Var. Media	67KSTF06MVX
	9 mm	19		90	33		22		FKM	Var. Media	67KSTF09MVX



## Plugs – without valve

## Series 65-67KS

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	Seal	Version	Part Number
 <p>Female Thread</p>	G 1/4 right	17		46	10					Oxygen	65SSIW13MXX
	G 3/8 right	19		46	10					Oxygen	65SSIW17MXX
	G 1/4 left	17		46	10					Fuel gas	66SSIL13MXX
	G 3/8 left	19		46	10					Fuel gas	66SSIL17MXX
	G 1/4 left	17		46	10					Var. Media	67SSIL13MXX
	G 3/8 left	19		46	10					Var. Media	67SSIL17MXX
 <p>Hose Barb</p>	6 mm			60	28					Oxygen	65SSTF06MXX
	9 mm			60	28					Oxygen	65SSTF09MXX
	6 mm			60	28					Fuel gas	66SSTF06MXX
	9 mm			60	28					Fuel gas	66SSTF09MXX
	6 mm			60	28					Var. Media	67SSTF06MXX
	9 mm			60	28					Var. Media	67SSTF09MXX